

AL 23 Sanduna – Fine/Medium

Product Description

AL23 Sanduna is a specially developed, flexible 100% acrylic resin emulsion roll-on texture coating. Formulated using high-durability acrylic resins blended with highest quality calcium carbonates and high purity quartz sands. **AL23 Sanduna** provides a soft matt finish, with an even sand texture appearance over various substrates.

Features & Performance Qualities

- Excellent adhesion properties.
- Flexible, impact resistant, highly water-resistant roll-on finish.
- Provides long-term Exterior Façade protection
- Available in fine & medium grades
- Moisture vapour permeable
- Ready to use.

Uses

- **AL23 Sanduna** is suitable for application over most, suitably prepared masonry substrates, such as bricks, blocks, F.C. Sheeting, A.A.C. blocks & panels and cement renders. Also, concrete, tilt-up and off-form concrete.
- Suitable for use both internally and externally
- **AL23 Sanduna** provides a durable, weatherproof, low maintenance finish. with over-coated with suitable water-based sealers for extended durability.

Typical product data

(@ 25°C and 50% Relative Humidity)

| | |
|---------------------|--|
| Coverage: | 60 - 70m ² / 15Lt. per coat |
| Drying/Curing: | 12 Hours |
| Over-coating: | Can be over-coated after min. 4 hours curing. |
| Touch Dry: | approx. 1 Hour |
| Dry Film Thickness: | |
| Colour: | Available in White, Mid and Deep Base (Tint using universal tinters for water-based products.) |
| Packaging: | 15Lt Bucket. |
| Clean-up: | Clean with water. |

AL 23 Sanduna Fine/Medium

Application

AL 23 Sanduna is designed for application with long Nap Rollers and comes ready to use.

- Ensure substrate is of sound nature, free from dust, dirt, loose particles and/or any other contaminants which may affect adhesion of subsequent coatings.
- Stir prior to application.
- Apply product with a Long-nap paint roller. Ensure to keep a wet-edge during application process.
- Apply a minimum of 2 coats to achieve optimum coverage and texture uniformity. (Observe recommended drying times between coats.)

Precautions and Limitations.

AL 23 Sanduna should not be applied in temperatures below 5°C or above 35°C. Avoid application in extremely windy conditions.

Protect from rain for up to 24hrs after application. (Depending on Climatic conditions.)

AL 23 Sanduna should not be applied over hot substrates, as workability and quality of finish may be affected.

AL 23 Sanduna is not suitable for application to areas of sustained damp, or areas submerged in water.

Transport, Storage & Handling

Store containers in a cool place, out of direct sunlight.

Protect product from freezing and extreme heat. Keep stored between 5°C - 35°C.

Do not stack over 3 drums high.

Disclaimer

Any advice, recommendations, information, assistance, or service provided by SUPA COAT AUSTRALIA PTY. LTD. Its staff or consultants in relation to products, their use and application is given in good faith and is believed by SUPA COAT AUSTRALIA PTY. LTD. to be appropriate and accurate. SUPA COAT AUSTRALIA PTY. LTD. will not accept responsibility for any misuse product/s or if not applied by suitably qualified, skilled and experienced persons and not in accordance with technical specifications. SUPA COAT technical information is correct at time of publication, however due to continuing product improvement, SUPA COAT AUSTRALIA PTY. LTD. reserves its right to change technical information without notice. It remains the sole responsibility of user to ensure information is current prior to use.